



# **Material Safety Data Sheet**

according to 91/155/EEC, modified by 1272/2008

# 1 - Product and Company Information

PRODUCT NAME Screw-Die-Clean

800ML/1kg

COMPANY AJ Solutions

Vierselbaan 40, unit 14/15

B-2240 Zandhoven

Telephone: +32 (0) 3 366 24 55

TECHNICAL PHONE Tel. +32 (0) 3 366 24 55

EMERGENCY PHONE Tel. +32 (0) 3 366 24 55

E-MAIL info@ajsolutions.be

# 2 - Composition/Information on Ingredients

Substances which are present in a percentage superior to the limits of exemption and present a danger for the health and/or the environment and/or a common limit value for the working place

Ingredient Name	Content	CAS#	EC no	R
	%			
Aluminium oxide	< 25	1344-28-1	215-691-6	R37,S2,S22 ,S24/25
Ammonia aqueous	< 2	1336-21-6	215-647-6	H314-H335- H400
Naphta Hydrotreated	< 1	64742-48-9	265-150-3	H304
Isotridecanol ethoxylated	< 25	9043-30-5	500-027-2	H302-H318
Water	< 25	7732-18-5	231-791-2	



Date Updated:01.01.2019

### 3 - Hazards Identification

### SPECIAL INDICATION OF HAZARDS TO HUMAN AND THE ENVIROMENT

Date Printed: 12.01.23



## 3.1

H317 – May cause an allergic skin reaction

H319 - Causes serious eye irritation

H355 – May cause respiratory irritation

P301-312: If swallowed call a poison centre or doctor, if you feel unwell

P304-340: If inhaled remove victim to fresh air and keep at rest in a position comfortable for

breathing

P302-352: If on skin wash with plenty of soap and water

### 4 - First Aid Measures

#### AFTER INHALATION

If inhaled, remove to fresh air.

### AFTER EYE CONTACT

In case of contact with eyes, flush with copious amounts of water for at least 15 minutes. Assure adequate flushing by separating the eyelids with fingers. Call a physician.

### AFTER SKIN CONTACT

In case of contact, immediately wash skin with soap.

### AFTER INGESTION

If swallowed, wash out mouth with water provided person is conscious. Induce no vomiting. Call a physician.

# 5 - Fire Fighting Measures

### **EXTINGUISHING MEDIA**

Suitable: Water spray. Carbon dioxide, dry chemical powder or appropriate foam.

Unsuitable: Water jet

### SPECIAL RISKS

Specific Hazards: Emits toxic fumes under fire conditions.

### SPECIAL PROTECTIVE EQUIPMENT FOR FIREFIGHTERS



## Date Updated:01.01.2019

Wear protective clothing to prevent contact with skin and eyes.

# 6 - Accidental Release Measures

# PERSONAL PRECAUTION PROCEDURES TO BE FOLLOWED IN CASE OF LEAK OR SPILL

Date Printed: 12.01.23

Avoid contact with eyes or skin.

### **ENVIRONMENT PRECAUTION**

If leakage occurs, dam up.

Prevent surface and ground-water infiltration, as well as ground penetration

### METHODS FOR CLEANING UP

Absorb on sand or vermiculite and place in closed containers for disposal. Ventilate area and wash spill site after material pickup is complete.

# 7 - Handling and Storage

#### **HANDLING**

Directions for Safe Handling: Do not breathe vapour. Avoid contact with eyes and skin.

### **STORAGE**

Conditions of storage

Keep tightly closed

Keep away from heat and open flame

Protect against direct sun light

# 8 - Exposure Controls/Personal Protection

### **ENGINEERING CONTROLS**

An eye bath.

# GENERAL HYGIENE MEASURES

Wash thoroughly after handling.

### **EXPOSURE LIMITS - GERMANY**

Aluminium oxide 6 mg/m³
Ammonia 14 mg/m³
Petroleum 200 mg/m3

### PERSONAL PROTECTIVE EQUIPMENT

Hand Protection: Working gloves

Eye Protection: Chemical safety goggles Body Protection: Normal working clothing



# 9 - Physical and Chemical Properties

Appearance Physical State: viscose fluid

Colour: white Odour: ammonia

BP/ BP Range (°C) 100 (water) = 212°F

Flash point (°C) 177 (DIN 51755) = 350,6°F

Viscosity 4000 mPas (25°C)

3100 mPas (40°C)

Density (g/cm<sup>3</sup>) 1,28

Solubility with water mixable



# 10 - Stability and Reactivity

STABILITY

Stable: stable

Conditions to avoid: high temperatures in the warehouse

Materials to avoid: Strong oxidizing agents

#### HAZARDOUS DECOMPOSITION PRODUCTS

Hazardous Decomposition Products: Carbon monoxide, Carbon dioxide

# 11 - Toxicological Information

Acute Toxicity

Ammonia LD50 (oral, rat) 350 mg/kg

Glycerine LD50 (oral, rat) > 12600 mg/kg.

Chronic effect N/A
Sensitizing effect N/A
Carcinogenic effect N/A
Mutagenic effect N/A
Reproductively effect N/A
Narcotic effect N/A

# **EXPOSITION**

Skin contact: Can produce skin irritation Eye contact: Can excite the eyes

Inhalation: Inhalation can damage your health. The product can irritate the mucous

membranes and the upper respiratory tract.

# 12 - Ecological Information

WGK (Germany) 2
Self classification: yes
Degradability: not
Aquatic toxicity: N/A
Eco-toxicity: N/A

Avoid contact with natural water.

### 13 - Disposal Considerations

### SUBSTANCE DISPOSAL

Note directions especially European, national and regional directions.

### DISPOSAL PACKAGING MATERIAL

Note directions especially European, national and regional directions.



# 14 - Transport Information

RID/ADR Non-hazardous for road transport.



# 15 - Regulatory Information

Not hazardous according to Directive 67/548/EEC

### 16 - Other Information

#### WARRANTY

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate to safety precautions. Cempex Europe shall not be held liable for any damage resulting from handling or from contact with the above product

### **DISCLAIMER**

Only for the commercial use. Not for drug, household or other uses. License granted to make unlimited paper copies for internal use only.

N/A = Not Assignable